

30 Amp, 3Ø 480 and 3Ø 600 Volts AC
3 Pole, 4 Wire, Grounding



**30A 3Ø 480V AC
NEMA L16-30R
10 HP** **30A 3Ø 600V
AC NEMA
L17-30R**

**Connector Bodies
Watertight Safety-Shroud®**

IP66 SUITABILITY UL Type 4X, 12

Description	Cord Dia.	Catalog Number	
Black Valox® housing, white Valox clamps.	.350"-1.150" (9-29)	HBL2733SW	HBL2743SW



HBL2733SW

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.350"-1.150" (9-29)	HBL2733	HBL2743
Black and white nylon, spring termination.	.350"-1.150" (9-29)	HBL2733ST	—
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	HBL27CM33	HBL27CM43



HBL2733

Note: See pages C-52 and C-53 for accessories.

Receptacles

Watertight Safety-Shroud

IP66 SUITABILITY UL Type 4X, 12


Description	Catalog Number	
Gray Valox housing and flange, back wired.	HBL2730SW	HBL2740SW

Note: See page C-54 for accessories.

Safety-Shroud® Twist-Lock®

IP20 SUITABILITY

Description	Catalog Number	
Gray Valox angle housing, one gang, back wired.	HBL2730AR	HBL2740AR
Gray Valox surface mounting, one gang, back wired.	HBL2730SR	HBL2740SR
Gray Valox semi-flush, two gang, back wired.	HBL2730SR2	HBL2740SR2



HBL2730SW

Single Flush Receptacles

IP20 SUITABILITY


Description	Catalog Number	
Black nylon face, back and side wired.	HBL2730	HBL2740
Black and white nylon, spring termination.	HBL2730ST	—

Note: See page C-52 for accessories.


Insulgrip Flanged Receptacles

Description	Catalog Number	
Nylon casing, back wired.	HBL2736	HBL2746
Nylon casing, back wire, spring termination.	HBL2736ST	—


Note: See page C-52 for accessories.




HBL2730ST




HBL2736



HBL2730



HBL2730SR2



HBL2730SR

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)