

# 30A Twist-Lock Devices

**30 Amp, 3ØY 120/208,  
277/480 and 347/600  
Volts AC, 4 Pole, 4 Wire,  
Non-Grounding**

**IP20**  
SUITABILITY



30A 3ØY 120/208V AC NEMA L18-30P 3 HP	30A 3ØY 277/480V AC NEMA L19-30P 10 HP	30A 3ØY 347/600V AC NEMA L20-30P
--	---	---

## Plugs

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2751	HBL2761	HBL2771

Note: See page C-53 for accessories.



HBL2751

## Flanged Inlets

Description	Catalog Number		
Nylon casing, back wired.	HBL2755	HBL2765	HBL2775

Note: See page C-52 for accessories.

**IP20**  
SUITABILITY




30A 3ØY 120/208V AC NEMA L18-30R 3 HP	30A 3ØY 277/480V AC NEMA L19-30R 10 HP	30A 3ØY 347/600V AC NEMA L20-30R
--	---	---

## Connector Bodies

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2753	HBL2763	HBL2773

Note: See pages C-52 and C-53 for accessories.



HBL2755



HBL2753

## Single Flush Receptacles


Description	Catalog Number		
Black nylon face, back and side wired.	HBL2750	HBL2760	HBL2770

Note: See page C-52 for accessories.


## Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	HBL2756	HBL2766	HBL2776

Note: See page C-52 for accessories.  
See page C-69 for technical information on Twist-Lock devices.



HBL2750



HBL2756

Dimensions in Inches (mm)