

30 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC, 4 Pole, 5 Wire, Grounding



30A 3ØY 120/208V AC NEMA L21-30R 3 HP	30A 3ØY 240/415V AC NEMA L26-30R	30A 3ØY 277/480V AC NEMA L22-30R 10 HP	30A 3ØY 347/600V AC NEMA L23-30R
--	--	---	--

Connector Bodies

Watertight Safety-Shroud®

IP66 SUITABILITY

UL Type 4x, 12

Description	Cord Dia.	Catalog Number			
Black Valox® housing, white Valox clamps.	.350"-1.150" (9-29)	HBL2813SW	HBL2803	HBL2823SW	—



HBL2813SW

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number			
Black and white nylon.	.350"-1.150" (9-29)	HBL2813	—	HBL2823	HBL2833
Black and white nylon, spring termination.	.350"-1.150" (9-29)	HBL2813ST	—	HBL2823ST	—
Spring termination, all black		HBL2813STBK	—	—	—
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	HBL28CM13	—	—	—
Black and white for flat cable.	.350"-1.150" (9-29)	HBL2813FC	—	—	—
All black nylon.	.350"-1.150" (9-29)	HBL2813BK	—	—	—



HBL2813ST



HBL2813

Note: See pages C-52 and C-53 for accessories.

Receptacles

Watertight Safety-Shroud

IP66 SUITABILITY

UL Type 4x, 12

Description	Catalog Number			
Gray Valox housing and flange, back wired.	HBL2810SW	—	HBL2820SW	HBL2830SW

Note: See page C-54 for accessories.



HBL2810SW

Safety-Shroud Twist-Lock

IP20 SUITABILITY


Description	Catalog Number			
Gray Valox angle housing, one gang, back wired.	HBL2810AR	—	—	—
Gray Valox surface mounting, one gang, back wired.	HBL2810SR	—	—	—
Gray Valox semi-flush, two gang, back wired.	HBL2810SR2	—	—	—

Single Flush Receptacles

IP20 SUITABILITY

Description	Catalog Number			
Black nylon face, back and side wired.	HBL2810	HBL2800	HBL2820	HBL2830
Black and white nylon, spring termination	HBL2810ST	—	HBL2820ST	—
Isolated ground, orange nylon face, back and side wired.	IG2810	—	—	—
Ring terminal connection.	HBL2810RT	—	—	—

Note: See page C-52 for accessories.




HBL2820ST

Insulgrip Flanged Receptacles

Description	Catalog Number			
Nylon casing, back wired.	HBL2816	—	HBL2826	HBL2836
Nylon casing, back wire, spring termination.	HBL2816ST	—	HBL2826ST	—
Black nylon casing, back wire, spring termination.	HBL2816STBK	—	—	—

Note: See page C-52 for accessories.



HBL2810SR

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)