Twist-Lock® Devices

Non-NEMA 20 Amp, 250, 125/250 Volts and 3ØY 120/208 Volts AC 2 Pole, 3 Wire, Grounding and 3 Pole, 3 Wire, Non-Grounding

For Replacement Use Only







Connector Bodies

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.360"930" (9-24)	HBL7314GCB	HBL7314C
Corrosion resistant, yellow nylon.	.360"930" (9-24)	-	HBL73CM14C

Note: See page B-52 for accessories.

Single Flush Receptacles

Description	Catalog Number	
Black nylon face, back wired.	HBL7310BG	HBL7310B

Note: See page B-52 for accessories.

Flanged Receptacles

Catalog Number	
-	HBL3326C

Note: See page B-52 for accessories.

For Replacement Use Only







Connector Bodies

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.350"-1.150" (9-29)	HBL7413GCB HBL7413C	

Note: See page B-52 for accessories.

Single Flush Receptacles

Description	Catalog Number	
Black thermoset, back wired.	HBL7410BG	HBL7410B
Mounted on a 4" (101.6) round metal cover.	-	HBL7417B

Note: See page B-52 for accessories.

Flanged Receptacles

Description	Catalog Number
Nylon casing, back wired.	- HBL7409C

Note: See page B-52 for accessories.

The devices shown on this page are not listed by Underwriters Laboratories Inc. and are for replacement use only in existing installations.

www.hubbell.com/wiringdevice-kellems/en



HBL7314C




HBL7310B





HBL7413GCB



HBL7410BG



Dimensions in Inches (mm)

CAUTION: To avoid electrical shock, review premises carefully and do not use if slot or blade configuration (design) is already in a circuit having a rating differing from the rating of this device.