


# Twist-Lock® Devices

**Non-NEMA 30 Amp, 250, 125/250 Volts and 3ØY 120/208 Volts AC  
2 Pole, 3 Wire, Grounding and  
3 Pole, 3 Wire, Non-Grounding**

For Replacement Use Only

**IP20**  
SUITABILITY



## Insulgrip® Plugs

Description	Cord Dia.	Catalog Number
Black and white nylon.	.360"-.930" (9-24)	<b>HBL3331GC</b> <b>HBL3331C</b>

Note: See page B-52 for accessories.




**HBL3331GC**

## Insulgrip® Flanged Inlets

Description	Catalog Number
Nylon casing, back wired.	- <b>HBL3334C</b>


Note: See page B-52 for accessories.



**HBL3334C**

For Replacement Use Only

**IP20**  
SUITABILITY



## Insulgrip® Plugs

Description	Cord Dia.	Catalog Number
Black and white nylon.	.350"-1.150" (9-29)	<b>HBL3431GCB</b> <b>HBL3431C</b>

Note: See page B-52 for accessories.

The devices shown on this page are not listed by Underwriters Laboratories Inc. and are for replacement use only in existing installations.



**HBL3431C**

**CAUTION: To avoid electrical shock, review premises carefully and do not use if slot or blade configuration (design) is already in a circuit having a rating differing from the rating of this device.**

Dimensions in Inches (mm)