



**15 Amp, 125, 250 Volts and 277 Volts AC
2 Pole, 3 Wire, Grounding**


IP20
SUITABILITY




HBL4720C




HBL4720CA




HBL24W47



HBL4723VY



HBL4716C



HBL4716

Dimensions in Inches (mm)

Plugs

| Description | Cord Dia. | Catalog Number | | |
|--|---------------------------|-----------------------------------|-----------------------------------|------------------------------------|
| | | 15A 125V NEMA L5-15P 0.5 HP | 15A 250V NEMA L6-15P 1.5 HP | 15A 277V AC NEMA L7-15P 2 HP |
| Insulgrip plug, black and white nylon. Multiple drive screws. Fed Spec WC596 | .230"-.720" (5.8-18.3) | HBL4720C | HBL4570C | HBL4770C |
| Insulgrip plug, black and white, spring termination Fed Spec WC596 | .230"-.720" (5.8-18.3) | HBL4720CST | HBL4570CST | HBL4770CST |
| All black nylon. | .230"-.720" (5.8-18.3) | HBL4720CBK | - | - |
| Insulgrip angle plug, 8 position angle, black and white nylon. Multiple drive screws. | .325"-.655" (8.3-16.6) | HBL4720CA | HBL4570CA | HBL4770CA |
| Insulgrip plug, corrosion resistant, yellow and white nylon. Multiple drive screws. Fed Spec WC596 | .230"-.720" (5.8-18.3) | HBL47CM20C | HBL45CM70C | HBL47CM70C |
| Elastogrip® plug, yellow elastomer, dust tight. | 300"-.655" (7.6-16.6) | HBL2447 | - | - |
| Elastogrip plug, yellow elastomer, water/dust tight. | 300"-.655" (7.6-16.6) | HBL24W47 | - | - |
| Valise® plug, yellow nylon. | .220"-.660" (5.6-16.8) | HBL4723VY | HBL4573VY | HBL4773VY |
| Valise® plug, black nylon. | .220"-.660" (5.6-16.8) | HBL4723VBK | HBL4573VBK | HBL4773VBK |

Note: See page B-51 for accessories.

Flanged Inlets

| Description | Catalog Number | | |
|---|-------------------|-----------------|-----------------|
| Insulgrip flanged inlet, nylon casing, back wired. | HBL4716C | HBL4586C | HBL4786C |
| Stainless steel casing, brown phenolic. | HBL4716* | HBL4586* | HBL4786* |
| Corrosion resistant, stainless steel casing, yellow melamine. | HBL47CM16* | - | - |

Note: See page B-50 for accessories.

HP ratings are AC only.

Only plugs are HP rated.

See page B-69 for technical information on Insulgrip devices.

*These flanged inlets will not accept Valise® connector bodies.