Straight Blade Devices 15A, 125V, 2 Pole, 3 Wire Grounding Flanged Receptacles

HUBBELL

Features

- Impact resistant thermoplastic construction
- Backwired terminations for ease of installation
- #8-32 Multiple drive terminal screws
- Mounting screws included

Ordering Information

Description Device Color Catalog Number Nylon casing, back White 783585173603 HBL5279C wired

Listings

UL Listed, File E2186 Certified to CSA, C22.2, No. 42 NEMA® WD-6 Compliant

Specifications

Housing Nylon Terminal Retainer Clear polycarbonate Contacts

Terminal Screws #8-32 Brass, Multiple Drive **Terminal Clamp** Cold rolled steel - nickel plated

Steel - nickel plated Assembly Screws Mounting Screws Nickel plated brass

Performance

Electrical

Current Interrupting Certified for current interrupting at full rated current

Withstands 2,000V minimum Dielectric Voltage

Mechanical

Product Identification Ratings are a permanent part of the device


Terminal Accommodation #18-#10 AWG copper stranded or solid conductor only Terminals identified in accordance with UL 498 and CSA Terminal Identification


Environmental

Flammability UL 94 V-2

Operating Temperatures Maximum continuous 75°C; minimum -40°C (w/o impact)







Accessories

WP1 Weatherproof Lift Cover

Resources

Customer Use Drawing eCatalog

