




HBL5266C




HBL5266CST




HBL5266CA




HBL1447



HBL14W47



HBL5965VY



HBL5966VBLK

Dimensions in Inches (mm)

IP20
SUITABILITY



15A 125V
NEMA 5-15P
UL CSA



20A 125V
NEMA 5-20P
UL CSA

Plugs

Insulgrip®

| Description | Cord Diameter | Catalog Number | |
|--|------------------------|---------------------|---------------------|
| Black and white nylon. | .230"-.720" (5.8-18.3) | HBL5266C | HBL5366C |
| Black and white, spring termination | .230"-.720" (5.8-18.3) | HBL5266CST | HBL5366CST |
| Blue and white nylon. | .230"-.720" (5.8-18.3) | HBL5266CBL | - |
| Black nylon extra large cord clamp. | .360"-.720" (9.1-18.3) | HBL5266EBK | HBL5366EBK |
| Black, spring termination | .230"-.720" (5.8-18.3) | HBL5266CBKST | HBL5366CBKST |
| Corrosion resistant yellow nylon. | .230"-.720" (5.8-18.3) | HBL52CM66C | HBL53CM66C |
| Corrosion resistant yellow nylon, spring termination | | HBL52CM66CST | HBL53CM66CST |
| 8-position angle plug, black and white nylon. | .325"-.655" (8.3-16.6) | HBL5266CA | HBL5366CA |
| 8-position angle plug, transparent enclosure. | .325"-.655" (8.3-16.6) | HBL5266CAT | - |
| Anchor lock, black and white nylon. | .230"-.720" (5.8-18.3) | HBL5280C* | - |
| Anchor lock, corrosion resistant yellow nylon. | .230"-.720" (5.8-18.3) | HBL52CM80C* | - |
| Finger grip, black neoprene, combination screws. CSA only. | .31"-.43" (7.9-10.9) | HBL5921 | - |
| Fusible, black vinyl housing, slotted screws. CSA only. | .296"-.625" (7.5-15.9) | HBL5299 | - |

Elastogrip®

| Description | Cord Diameter | Catalog Number | |
|--|------------------------|-------------------|-------------------|
| Yellow elastomer, dust tight. IP20 SUITABILITY. | .300"-.655" (7.6-16.6) | HBL1447 | HBL1433 |
| Yellow elastomer, watertight. IP20 and IP55 SUITABILITY. | .300"-.655" (7.6-16.6) | HBL14W47** | HBL14W33** |
| Yellow elastomer, watertight. IP65, 66, 67 SUITABILITY. | .375"-.625" (9.5-15.9) | HBL14W47A | HBL14W33A |

Valise®

IP20
SUITABILITY

| Description | Cord Diameter | Catalog Number | |
|--|------------------------|--------------------|--------------------|
| Yellow nylon. | .220"-.660" (5.6-16.8) | HBL5965VY | HBL5364VY |
| Black nylon. | .220"-.660" (5.6-16.8) | HBL5965VBLK | HBL5364VBLK |
| Gray nylon. | .220"-.660" (5.6-16.8) | HBL5965VGY | - |
| Orange nylon, sold in bulk pack of 50. | .220"-.660" (5.6-16.8) | HBL515PVO | - |
| Insulation displacement terminals, black nylon. | .230"-.360" (5.8-9.1) | HBL5966VBLK | - |
| Insulation displacement terminals, yellow nylon. | .230"-.360" (5.8-9.1) | HBL5966VY | - |

Note: *UL Component Listed only. Not for general use applications.

**Watertight plugs IP55 suitability when installed and used properly with mating Elastogrip watertight connector bodies.

Horsepower ratings listed are AC only.

See page A-48 for accessories.