




**15A 250V  
NEMA 6-15P  
UL CSA  
1.5 HP**



**20A 250V  
NEMA 6-20P  
UL CSA  
2 HP**

## Plugs


Description	Cord Diameter	Catalog Number	
Insulgrip® Plug, black and white nylon.	.230"-.720" (5.8-18.3)	<b>HBL5666C</b>	<b>HBL5466C</b>
Insulgrip plug, black and white, spring termination	.230"-.720" (5.8-18.3)	<b>HBL5666CST</b>	<b>HBL5466CST</b>
Insulgrip® Plug, corrosion resistant, yellow nylon.	.230"-.720" (5.8-18.3)	<b>HBL56CM66C</b>	<b>HBL54CM66C</b>
Insulgrip plug, corrosion resistant, spring termination, yellow	.230"-.720" (5.8-18.3)	<b>HBL56CM66CST</b>	<b>HBL54CM66CST</b>
8-Position Insulgrip® Angle Plug, black and white nylon.	.325"-.655" (8.3-16.6)	<b>HBL5666CA</b>	<b>HBL5466CA</b>
Valise® Plug, yellow nylon.	.220"-.660" (5.6-16.8)	<b>HBL5666VY</b>	<b>HBL5464VY</b>



**HBL5666C**



**HBL5666CST**



**HBL5669C**

## Connector Bodies

Description	Cord Diameter	Catalog Number	
Insulgrip® Connector Body, black and white nylon, multiple drive screws.	.230"-.720" (5.8-18.3)	<b>HBL5669C</b>	<b>HBL5469C</b>
Insulgrip Connector Body, Black and White, Spring Termination	.230"-.720" (5.8-18.3)	<b>HBL5669CST</b>	<b>HBL5469CST</b>
Valise® Connector Body, yellow nylon.	.220"-.660" (5.6-16.8)	<b>HBL5669VY</b>	<b>HBL5469VY</b>


Note: See page A-48 for accessories.




**15A 250V  
NEMA 6-15R  
UL CSA**



**20A 250V  
NEMA 6-20R  
UL Listed**



**HBL5669C**



**HBL5666CA**

## Insulgrip® Flanged Inlets

Description	Catalog Number	
Nylon casing, back wired.	<b>HBL5678C</b>	<b>HBL5478C</b>


Note: Flanged inlets are not HP rated.  
See page A-48 for accessories.



**15A 250V  
NEMA 6-15P  
UL CSA**



**20A 250V  
NEMA 6-20P  
UL CSA**



**HBL5666VY**

## Flanged Receptacles

Description	Catalog Number	
Nylon casing, multiple drive screws.	<b>HBL5679C</b>	<b>HBL5479C</b>
Stainless steel flange, brown phenolic housing (mounting screws packaged separately).	<b>HBL5656</b>	-


Note: Connector bodies are not HP rated.  
See pages A-47 and A-48 for accessories.



**15A 250V  
NEMA 6-15R  
UL CSA**



**20A 250V  
NEMA 6-20R  
UL Listed**



**HBL5678C**

For quick visual identification of circuits or configurations.

## Colored Cord Clamps\*

Description	Color	Catalog Number
For use with 15A and 20A, 2 pole/3 wire, insulgrip plugs and connectors with cord diameter range of .230"-.720" (5.8-18.3) only.	Blue	<b>HBLCORDCLAMPBL</b>
	Green	<b>HBLCORDCLAMPGN</b>
	Orange	<b>HBLCORDCLAMPOR</b>
	Purple	<b>HBLCORDCLAMPPP</b>
	Red	<b>HBLCORDCLAMPR</b>
	Yellow	<b>HBLCORDCLAMPY</b>

Note: \*Clamp only. Contains no screws. Order in increments of 10. Not UL Listed or CSA Certified.



Dimensions in Inches (mm)