



**HBLPOB1**



**White POB**



**Cover Plates**



**Deluxe Cord Grips  
(purchased separately)**



**Gray Nylon  
Cord Connector**

## Heavy Duty Portable Outlet Boxes and Cover Plates

Description	Catalog Number
Box with cord strain relief, with one blank cover plate.	<b>HBLPOB1</b>
White box with cord strain relief, one blank white cover plate.	<b>HBLPOB1L</b>
Box with cord strain relief, with one blank cover plate, black.	<b>HBLPOB1BK</b>
Box with cord strain relief, with two duplex (indoor) cover plates.	<b>HBLPOB1D</b>
White box with cord strain relief, with two white duplex (indoor) cover plates.	<b>HBLPOB1DL</b>
Box with cord strain relief, with two duplex (indoor), yellow cover plates.	<b>HBLPOB1DY</b>
Blank, non-metallic FS cover plate with foam gasket, gray.	<b>HBLP14FS</b>
Blank, non-metallic FS cover plate with foam gasket, white.	<b>HBLP14FSL</b>
Duplex, non-metallic FS cover plate, gray.	<b>HBLP8FS</b>
Duplex, non-metal FS cover plate, white.	<b>HBLP8FSL</b>
Duplex, non-metallic FS cover plate, yellow.	<b>HBLP8FSY</b>
Single receptacle (1.39"), non-metallic FS cover plate, gray.	<b>HBLP7FS</b>
Single receptacle (1.56"), non-metallic FS cover plate, gray.	<b>HBLP720FS</b>
Rectangular opening, non-metallic FS cover plate, gray.	<b>HBLP26FS</b>
Rectangular opening, non-metallic FS cover plate, White.	<b>HBLP26FSL</b>

## Other Cover Plates and Devices

### which may be used with Heavy Duty Portable Outlet Boxes

Description	Catalog Number
Duplex cover plate, weatherproof.	<b>HBL5221, HBL52CM21</b>
Single receptacle (1.39") cover plate, weatherproof.	<b>HBL7423WO, HBL74CM23WO</b>
Single receptacle (1.56") cover plate, weatherproof.	<b>HBL7425WOA, HBL74CM25WOA</b>
Safety-Shroud Twist-Lock® surface receptacles.	<b>HBL2310SR, HBL2320SR, HBL2330SR, HBL2610SR, HBL2620SR</b>

Note: Standard product gray, CM yellow.

## Deluxe Cord Grips Straight Male Thread

### Nylon Fittings, Stainless Steel Mesh, Liquidtight, for Insulated Cables

Grip Diameter Range Inches (cm.)	Thread Size NPT (inches)	Form Size	Catalog Number
.375"-.500" (.97-1.27)	¾"	F3	<b>074011335</b>
.500"-.625" (1.27-1.59)	¾"	F3	<b>074011336</b>
.625"-.750" (1.59-1.90)	¾"	F3	<b>074011337</b>


## Nylon Cord Connector Straight Male Thread

Grip Diameter Range Inches (cm.)	Thread Size NPT (inches)	Form Size	Catalog Number
.375"-.500" (.97-1.27)	¾"	F3	<b>SHC1035CR</b>
.500"-.625" (1.27-1.59)	¾"	F3	<b>SHC1036CR</b>
.625"-.750" (1.59-1.90)	¾"	F3	<b>SHC1037CR</b>

## Specifications for Heavy Duty Portable Outlet Boxes and Cover Plates

UL Listed	UL 514C, UL467 and UL50 Enclosures Types 1, 3R.
CSA Certified	C22.2 No. 18 and C22.2 No. 94 Enclosures Types 1, 3R and C22.2 No. 0.4 (Impedance).
Box Specifications:	
Moisture Resistance	Wet and damp locations, Enclosure Type 3R when used with weatherproof cover plates. Dry, indoors locations, Enclosure Type 1 with all other cover plates. UL 94V-0, 94-5VA classification.
Flammability	80°C maximum; -35°C minimum.
Operating Temperature	All materials are UV stabilized.
UV Resistance	in accordance with UL 514C, UL50, C22.2 No. 18 and C22.2 No. 94.
Impact and Crush Resistance	Valox®.
Material	Nylon nut; Nylon Gotcha® ring; Neoprene grommet.
Cord Connector Materials	.38" to .75" diameter.
Cord Diameter Range	Brass.
Bonding Strap Material	Brass.
Threaded Inserts	Brass.
Grounding Screw Material	Brass.
Indoor Cover Plate Screws Material	Zinc Plated Steel.
Outdoor Cover Plate Screws Material	Stainless Steel.
Cover Plate Gasket Material	UL recognized closed-cell foam (aging and oil resistant).

## Dimensions



Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)