



30 Amp, 125/250 and 3Ø 250 Volts AC 3 Pole, 3 Wire, Non-Grounding and 3 Pole, 4 Wire, Grounding



30A 125/250V A0 NEMA L10-30R







			2 (2) 111	0111
Watertight Safety-Shroud®		IP66 SUITABILITY UL Type 4x, 12		
Description	Cord Dia.	Catalog Number		
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)	-	HBL2713SW	HBL2723SW
Reverse service, black Valox® housing, white Valox® clamps (use with HBL2715SWR), (Not shown).	.350"-1.150" (9-29)	-	HBL2713SR	-



HBL2713SW

Insulgrip [®]		IP20 SUITABILITY		
Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	_	HBL2713	HBL2723
Black and white nylon, spring termination	.350"-1.150" (9-29)	-	HBL2713ST	HBL2723ST
Black and white nylon, (Not shown).	.300"950" (7.6-24.1)	HBL2663	-	-
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	_	HBL27CM13	HBL27CM23
All black nylon.	.350"-1.150" (9-29)	_	HBL2713BK	_
Note: See page R-52 for accessories				



HBL2713

Note: See page B-52 for accessories.

Safety-Shroud® Twist-Lock®

Receptacles

Watertight Safety-Shroud®	IP66 SUITABILITY UL Type 4x, 12
Description	Catalog Number
Gray Valox® housing and flange, back wired.	- HBL2710SW HBL2720SW
Note: See page B 54 for accessories	




IP20 SUITABILITY

Description	Catalog Number		
Gray Valox® angle housing, one gang, back wired.	-	HBL2710AR	HBL2720AR
Gray Valox® surface mounting, one gang, back wired.	-	HBL2710SR	HBL2720SR
Gray Valox® semi-flush, two gang, back wired.	_	HBL2710SR2	HBL2720SR2

HBL2710SW

Single Flush Receptacles		IP20 SUITABILITY	
Description	Catalog Number		
Black nylon face, back and side wired.	-	HBL2710	HBL2720
Black and white nylon, spring termination.	-	HBL2710ST	HBL2720ST
Black nylon face, back and side wired, (Not shown).	HBL2660	-	-
Isolated ground, orange nylon face, back and side wired.	-	IG2710	IG2720
Ring terminal connection.	_	HBL2710RT	HBL2720RT
		· ·	



Note: See page B-52 for accessories.

Note: See page B-52 for accessories.

Insulgrip® Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	-	HBL2716	HBL2726
Nylon casing, back wire, spring termination	-	HBL2716ST	HBL2726ST

HBL2720ST







4.56° (115.8) 4.56° (72.1) HBL2710SR

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)