30 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC
4 Pole, 5 Wire, Grounding

Connector Bodies

Watertight Safety-Shroud®

IP66 SUITABILITY — UL Type 4x, 12

Description	Cord Dia.	Catalog Number	30A 3ØY 120/208V AC NEMA L21-30R 3 HP	30A 3ØY 240/415V AC NEMA L26-30R	30A 3ØY 277/480V AC NEMA L22-30R 10 HP	30A 3ØY 347/600V AC NEMA L23-30R
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)		**HBL2813SW**	**HBL2803**	**HBL2823SW**	–



HBL2813SW

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number				
Black and white nylon.	.350"-1.150" (9-29)		**HBL2813**	–	**HBL2823**	**HBL2833**
Black and white nylon, spring termination	.350"-1.150" (9-29)		**HBL2813ST**	–	**HBL2823ST**	–
Spring termination, all black			**HBL2813STBK**	–	–	–
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)		**HBL28CM13**	–	–	–
Black and white for flat cable.	.350"-1.150" (9-29)		**HBL2813FC**	–	–	–
All black nylon.	.350"-1.150" (9-29)		**HBL2813BK**	–	–	–

Note: See page B-52 for accessories.

HBL2813ST

HBL2813

Receptacles

Watertight Safety-Shroud®

IP66 SUITABILITY — UL Type 4x, 12

Description	Catalog Number			
Gray Valox® housing and flange, back wired.	**HBL2810SW**	–	**HBL2820SW**	**HBL2830SW**

Note: See page B-54 for accessories.



HBL2810SW

Safety-Shroud® Twist-Lock®

IP20 SUITABILITY

Description	Catalog Number			
Gray Valox® angle housing, one gang, back wired.	**HBL2810AR**	–	–	–
Gray Valox® surface mounting, one gang, back wired.	**HBL2810SR**	–	–	–
Gray Valox® semi-flush, two gang, back wired.	**HBL2810SR2**	–	–	–

Single Flush Receptacles

IP20 SUITABILITY

Description	Catalog Number			
Black nylon face, back and side wired.	**HBL2810**	**HBL2800**	**HBL2820**	**HBL2830**
Black and white nylon, spring termination	**HBL2810ST**	–	**HBL2820ST**	–
Isolated ground, orange nylon face, back and side wired.	**IG2810**	–	–	–
Ring terminal connection.	**HBL2810RT**	–	–	–

Note: See page B-52 for accessories.



HBL2820ST

Insulgrip® Flanged Receptacles

Description	Catalog Number			
Nylon casing, back wired.	**HBL2816**	–	**HBL2826**	**HBL2836**
Nylon casing, back wire, spring termination	**HBL2816ST**	–	**HBL2826ST**	–
Black nylon casing, back wire, spring termination	**HBL2816STBK**	–	–	–

Note: See page B-52 for accessories.

HBL2810SR

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)