# Straight Blade Devices

# 20A, 125V, 2 Pole, 3 Wire Grounding

#### **HBL® Extra Heavy Duty Specification Grade Duplex Receptacle**

#### **Features**

- Triangle marking on face indicates isolated ground
- Slender compact design
- Finder Groove Face

**Ordering Information** 

DescriptionDevice ColorUPCCatalog NumberIsolated ground, backOrange783585778402IG5362

#### Listings

UL Listed to UL498 File No. E2186 Certified to CSA, C22.2, No. 42 File 285 Fed. Spec. WC596 NEMA® WD-6 Compliant

### **Specifications**

Face Nylon
Base PBT
Contacts 0.031" (0.8) Brass
Clamp Nickel plated steel
Terminal Screws Brass
Mounting Strap .050 in. (1.3) Brass
Automatic Self-grounding Clip Stainless steel
Mounting Screws Zinc plated steel

## Performance

Electrical

Current Interrupting Certified for current interrupting at full rated current

Dielectric Voltage Withstands 2,000V minimum

Mechanical

Product Identification Ratings are a permanent part of the device
Terminal Accommodation #12-#10 AWG stranded or solid copper wire only
Terminal Identification Terminals identified in accordance with UL 498 and CSA

Environmental


Flammability Top: UL 94V-2, Base: UL 94V-0

Operating Temperatures Maximum continuous 75°C; minimum -40°C (w/o impact)

# HUBBELL







#### **Online Resources**

Customer Use Drawing eCatalog
Installation Instructions

#### **Accessories**

Wallplate or Weatherproof Cover Duplex Opening

