

**IP44**  
SUITABILITY



**Weatherproof Receptacle Lift Cover Plates for FS/FD Box Mounting**

Description	Catalog Number
Corrosion resistant, gray thermoplastic.	<b>HBL7774WO</b>
Same as above except yellow.	<b>HBL77CM74WO</b>
Cast aluminum.	<b>HBL7770</b>

Note: See page P-21 for additional information on weatherproof covers.



**HBL7770**

**Receptacle Plates for FS/FD Box Mounting**


Description	Catalog Number
Cast aluminum with lift cover.	<b>HBL7382**</b>
Same as above less lift cover.	<b>HBL7383*</b>
Stainless steel, single gang, wallplate.	<b>SS750†</b>



**SS750**

**Receptacle 1/2" Raised Cover**

Description	Catalog Number
Galvanized Steel fits 4" square or 2-gang box.	<b>HBL50SC‡</b>



**HBL50SC**

**Conduit Adapters for 50A Twist-Lock® Plugs and Connectors**

Description	NPT Thread Size	Catalog Number
Thermoplastic housing, conduit adapters for use with CS style 50A Twist-Lock® devices. Available in 1/2", 3/4" and 1" NPT thread sizes.	1/2"	<b>CS50CA05</b>
	3/4"	<b>CS50CA34</b>
	1"	<b>CS50CA10</b>

**IP55\*\***  
SUITABILITY

**Weatherproof Boots**

Description	Catalog Number
Seal-Tite® triple seal black elastomeric cover for plugs when used in a cord set and connector bodies when used with flanged inlets.	<b>HBL7716C‡</b>
Seal-Tite triple seal black elastomeric cover for connector bodies when used with cord sets.	<b>HBL7717C‡</b>



**CS50CA34**

**Inlet Closure Plug**

Description	Catalog Number
Black closure plug.	<b>HBL4892‡</b>



**HBL7716C**

**Replacement Parts**

Description	Catalog Number
Cord clamp Kit.	<b>HBLCSCK</b>

Note: \*Will only fit non-"CS" type 50A Twist-Lock receptacles.

\*Not UL Listed "WDL Closed".

\*\*When installed and used properly with plug and connector body combinations.

‡IP20 Suitability.

†Not UL Listed.



**HBL7717C**



**HBL4892**



**HBLCSCK**

Dimensions in Inches (mm)