

50 Amp, 125, 250 Volts and 480 Volts AC



**CS8265C**

**IP20**  
SUITABILITY



**50A 125V**  
UL/CSA



**50A 250V**  
UL/CSA




**50A 480V AC**  
UL/CSA

## Plugs

Description	Cord Dia.	Catalog Number		
Nylon housing, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	<b>CS6361C</b>	<b>CS8265C</b>	<b>CS8465C</b>

Note: See page B-60 for accessories.



**CS8275**

## Flanged Inlets

Description	Catalog Number		
Zinc plated steel casing, thermoset interior.	<b>CS6377</b>	<b>CS8275</b>	<b>CS8475†</b>

Note: †Not CSA Certified.



**CS8264C**

**IP20**  
SUITABILITY



**50A 125V**  
UL/CSA



**50A 250V**  
UL/CSA




**50A 480V AC**  
UL/CSA

## Connector Bodies

Description	Cord Dia.	Catalog Number		
Nylon housing, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	<b>CS6360C</b>	<b>CS8264C</b>	<b>CS8464C</b>

Note: See page B-60 for accessories.



**CS8269**

## Receptacles

Description	Catalog Number		
Black phenolic.	<b>CS6370</b>	<b>CS8269</b>	<b>CS8469†</b>

Note: See page B-60 for accessories.  
†Not CSA Certified.

Dimensions in Inches (mm)