



# UL iQ for Surge Protective Devices



Surge Protective Devices

E314042

Guide Information

## Schneider Electric USA, Inc.

Schneider Electric, SURGE PROTECTION BUSINESS, 1751 S 4800 W, Salt Lake City UT 84104

**Model(s): TVS2HWA50X\$, TVS2HWA80X\$, TVS2HWA10X\$, TVS2HWA12X\$\***

Permanently Connected

<u>SPD Type</u>	<u>Volts (V)</u>	<u>AC/DC DC PV</u>	<u>Phase</u>	<u>Amps (A)</u>	<u>Ambient Min(°C)</u>	<u>Ambient Max(°C)</u>	<u>Mode</u>	<u>VPR (Vpk)</u>	<u>MCOV (V)</u>	<u>In (kA)</u>	<u>SCCR (kA)</u>
2	208/120	AC	3Y	n/a	-35	85	L-L	1500	300	20	200
							L-N	900	150		
							L-G	1200	300		
							N-G	700	150		
2	220/127	AC	3Y	n/a	-	-	L-L	1500	300	20	200
							L-N	900	150		
							L-G	1200	300		
							N-G	700	150		

Evaluated to: UL 1449 4th Ed. Rev: 2018-08-01 and CSA C22.2 No. 269.2-13, 2013-06

\$ - May be followed by additional suffixes.

\* - Complementary Listed EMI Filters (FOKY), E314042.

Note - All models may be followed by additional suffixes.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2009-12-11

Last Revised: 2019-01-25

© 2019 UL LLC

