

Flush Rectangular Non-Metallic Floor Boxes with Non-Metallic Covers, for Use In Concrete Floor
ScrubShield® cULus
Complies with UL514A

Style	1-Gang	2-Gang	3-Gang
Min. Depth of Pour	3.00" (76.2)	3.00" (76.2)	3.00" (76.2)
Adjustability	Fully	Fully	Fully
Cubic Inch (cm ³)	14.3 cu. in. (234.3 cm ³)	14.3 cu. in. (234.3 cm ³)	14.3 cu. in. (234.3 cm ³)
Capacity per Gang	per 1" depth	per 1" depth	per 1" depth
Dimensions - A	6.00" (152.4)	6.00" (152.4)	6.00" (152.4)
Dimensions - B	3.60" (91.4)	6.80" (172.7)	10.04" (255.0)
Dimensions - C	5.47" (138.9)	5.47" (138.9)	5.47" (138.9)
Dimensions - D	6.90" (175.3)	6.90" (175.3)	6.90" (175.3)
Dimensions - E	5.41" (137.4)	8.56" (221.4)	11.75" (298.4)
Hubs	(4) 1-1/4"	(6) 1-1/4"	(8) 1-1/4"
Reducers	(4) 1" to 3/4" and (4) 1-1/4" to 1"	(6) 1" to 3/4" and (6) 1-1/4" to 1"	(8) 1" to 3/4" and (8) 1-1/4" to 1"
Concrete Cover Included	✓	✓	✓
Closure Plugs Included	✓	✓	✓
Low Voltage Barrier**	—	(1) Removable	(2) Removable

Note: UL File Number E92074.

*Suitable for single service applications only.

**Replacement low voltage barriers, 5 pack, catalog number PRFBLVDPK5.

Rectangular Metal Covers and Flanges
Flush Rectangular Metal Covers and Flanges

Required Components for Flush Tile Applications				Required Components for Flat Flange Applications				
Adapter Collar (One required per gang)		Adapter Frame with Grounding Wire (One required per gang) Dim. 4.36" x 3.20" x 0.30"		Adapter Collar (One required per gang)				
Gray	PFBRAC		Brass Aluminum	S5017GR SA5017GR		Gray	PFBRAC	

Flat Flanges*

Flat Flange Height 0.125"

Number of Gangs Dimensions	1-Gang 6.00" x 4.85"	2-Gang 6.00" x 8.13"	3-Gang 6.00" x 11.34"	
Brass, square edge Aluminum, square edge Brass, beveled edge Aluminum, beveled edge	SB3083W SA3083W SB3083WB SA3083WB	SB3084W SA3084W SB3084WB SA3084WB	SB3085W SA3085W SB3085WB SA3085WB	

Note: *Flange applications; square edge for carpet and recessed, beveled edge for use on hard finished surfaces.

Covers - One Required per Gang†

Brass Aluminum Dimensions 4.15" x 2.99"	S3825 SA3825	S3625 SA3625	S3625TR SA3625TR	S3826 SA3826	S2425 SA2425	S2625 SA2625	S2825 —	S3425 —	S3813 SA3813

Note: †COVER LOAD RATING; Metallic covers and flanges 2,000 lbs. with 2x safety factor Load applied through a 3 in. (76) mandrel at the center of the cover.

Dimensions in Inches (mm)