


Flush Rectangular Cast Iron Floor Boxes with Metal Covers, for Use In Concrete Floor

ScrubShield® cULus
Complies with UL514A

Style	Cast Iron					
	1-Gang Deep	2-Gang Deep	3-Gang Deep	1-Gang Shallow	2-Gang Shallow	3-Gang Shallow
						
Catalog Numbers	FB4133*	FB4233	FB4333	FB4114*	FB4214	FB4314
Cover Frame Material	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic
Min. Depth of Pour	3.50" (95.3)	3.50" (95.3)	3.50" (95.3)	2.00" (50.8)	2.00" (50.8)	2.00" (50.8)
Adjustability	Fully	Fully	Fully	Semi	Semi	Semi
Before Pour External Height Adjustment	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)
After Pour Internal Height Adjustment	.875" (22.2)	.875" (22.2)	.875" (22.2)	—	—	—
Cubic Inch (cm³) Capacity per Gang	33.0 (540.8)	36.5 (598.2)	36.5 (598.2); 34.8 (570.3) center gang	16.0 (262.2)	16.0 (262.2)	16.0 (262.2)
Dimensions – A	3.42" (87.0)	3.40" (86.4)	3.40" (86.4)	2.03" (51.4)	2.05" (51.9)	2.06" (52.2)
Dimensions – B	4.85" (123.2)	4.91" (124.7)	4.91" (124.7)	5.66" (143.7)	5.46" (138.7)	5.46" (138.7)
Dimensions – C	4.85" (123.2)	8.13" (206.5)	11.41" (289.8)	4.38" (111.3)	7.50" (190.4)	10.71" (272.0)
Dimensions – D	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)
Dimensions – E	3.20" (81.3)	6.42" (163.0)	9.64" (244.8)	3.20" (81.3)	6.42" (163.0)	9.64" (244.8)
Threaded Hubs	(4) 1"	(6) 1"	(8) 1"	(4) 3/4"	(4) 3/4"	(6) 3/4"
Concrete Cover Included	✓	✓	✓	✓	✓	✓
Closure Plugs Included	✓	✓	✓	✓	✓	✓
1" to 3/4" Threaded Reducer	2 Each	4 Each	4 Each	—	—	—
Low Voltage Barrier	—	(1) Removable	(2) Removable	—	Non-Removable	Non-Removable

Note: UL File Number E92074.

*Suitable for single service applications only.



Flush Rectangular Covers Flanges

Required Components for Flush Tile or Finished Concrete Applications

Brass Aluminum	S5017GR SA5017GR		Adapter Frame with Grounding Wire (One required per gang) Dim. 4.36" x 3.20" x 0.30".
-------------------	-----------------------------------	---	---

Flat Flanges*

Flat Flange Height 0.125"

Number of Gangs Dimensions	1-Gang 6.00" x 4.85"	2-Gang 6.00" x 8.13"	3-Gang 6.00" x 11.34"
Brass, square edge Aluminum, square edge Brass, beveled edge Aluminum, beveled edge	SB3083W SA3083W SB3083WB SA3083WB 	SB3084W SA3084W SB3084WB SA3084WB 	SB3085W SA3085W SB3085WB SA3085WB 

Note: *Flange applications; square edge for carpet and recessed, beveled edge for use on hard finished surfaces

Covers – One Required per Gang†

Brass Aluminum Dimensions 4.15" x 2.99"	S3825 SA3825 	S3625 SA3625 	S3625TR SA3625TR 	S3826 SA3826 	S2425 SA2425 	S2625 SA2625 	S2825 — 	S3425 — 	S3813 SA3813 
	Duplex Flap	Duplex Screw	Tamper Resistant Duplex Screw	Style Line® Decorator Opening	2-1/8" x 3/4" Combination	2-1/8" x 1" Combination	2-1/8" Single Receptacle	2-3/8" Single Receptacle	Blank

Note: †COVER LOAD RATING; Metallic covers and flanges 2,000 lbs. with 2x safety factor Load applied through a 3 in. (.76) mandrel at the center of the cover. Dimensions in Inches (mm)