



**3 Inch Core Hole Units,
 for Use In Concrete Floors**


ScrubShield® cUL US ULC LISTED
 Complies with UL514A

2X2 Flush FRPT, One-Piece Units (PT2X2FIT)



Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Poke-Through Non-metallic Cover.	Black/Aluminum Black/Aluminum Black Gray Black Gray	PT2X2ALU3 PT2X2IGALU3 PT2X2BL PT2X2GY PT2X2IGBL* PT2X2IGGY*	2X2 Poke-Through.	Black/Brass Brass Finish/Brass Black/Brass Brass Finish/Brass	PT2X2BRS3 PT2X2BRS PT2X2IGBRS3* PT2X2IGBRS*
Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks Painted or brushed aluminum flange Approved for use in the City of Chicago.			<ul style="list-style-type: none"> Pre-wired 20A Style Line decorator duplex receptacle and (2) Category 6 data jacks Solid brass flange Approved for use in the City of Chicago 		

Note: *Includes pre-wired 20A isolated ground Style Line® decorator duplex receptacle.



2X2 Flush FRPT, Two-Piece Units

Description	Catalog Number	
Multi-Channel Through-Floor Fitting with (1) 3/4 in. EMT stem with junction box for power and (2) 1/2 in. EMT stems for low voltage.	PT2X2FIT	
		Specifications: <ul style="list-style-type: none"> 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) For 2-1/4 in. to 7 in. floor thickness UL installation spacing – minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area Approved for use in the City of Chicago

Service Fittings

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Service Fitting Non-metallic Cover/ Aluminum Flange	Black/Aluminum Black Gray	PT2X2SFALU3 PT2X2SFBL PT2X2SFGY	2X2 Service Fitting Non-metallic Cover/ Brass Flange	Black/Brass Brass Finish/Brass	PT2X2SFBRS3 PT2X2SFBRS
<ul style="list-style-type: none"> Pre-wired 20A Style Line decorator duplex receptacle and (2) Category 6 data jacks Painted or brushed aluminum flange 			<ul style="list-style-type: none"> Pre-wired 20A Style Line decorator duplex receptacle and (2) Category 6 data jacks Solid brass flange 		

Accessories

Description	Color/Material	Catalog Number	Description	Color/Material	Catalog Number
Non-metallic Replacement Covers.	Brass Finish Black Gray	PT2X2CBRS PT2X2CBL PT2X2CGY	Closure Plug Textured aluminum plug seals 3 in. core hole when FRPT is no longer required and is removed; Maintains the floor's 1 – 4 hour fire rating; UL Listed and CSA Certified.	Gray	FRP250
					

Note: See page R-43 for technical information.

Dimensions in Inches (mm)