



Main

Product or component type	Meter Mains
Range of product	QO

Complementary

Line Rated Current	200 A
Short-circuit current	22 kA
Meter socket type	Ringed
Device mounting	Surface
Number of spaces	0
Product mounting	Surface
Number of circuits	0
Number of tandem circuit breakers	0
Hub type	A
Electrical connection	Lugs line side Lugs service ground
AWG gauge	AWG 4...250 kcmil (aluminium/copper) line side AWG 8...AWG 2/0 for 2 cable(s) (aluminium/copper) service ground
Device composition	Service disconnect (ordered separately)
Service disconnect rated current	200 A
Service feed location	OH UG
Bypass type	No bypass

Environment

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0944 - Schneider Electric declaration of conformity	Compliant - since 0944 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.