



BURNDY Catalog Number
UPC Number
Description
Status

YAV2CL2NT14FX
 7818102742177
 CULUG-2FLEX-1/4X5/8-NARO
 Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	2.26
Barrell Style	Chamfered
Bolt Hole Size (in)	0.27
Barrel Type	Standard
Thickness	0.10
B Length (in)	0.63
Pad Width (in)	0.48
E - in	0.63
Strip Length	11/16
General	
Number of Holes	2
Product Description	Copper Compression Lug, Narrow Tongue, 2 Hole w/ Inspection Window, 2 Flex, 1/4" Stud, 5/8" Stud Hole Spacing, Short Barrel, Tin Plated
Conductor(s)	
Flex (Class G) Size - Range	2 AWG
Flex (Class H) Size - Range	2 AWG
Flex (Class I) Size - Range	2 AWG
Copper Solid Size (Range)	2 AWG
DLO Size (Range)	3 (125/#24) DLO-2 (150/#24) DLO
Copper Stranded (Range)	2 AWG
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/4
Color Code	Brown
Plated (Yes or No)	Y
Index Number	10
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175