



BURNDY Catalog Number
UPC Number
Description
Status

YA2CL2NT14
 7818102103833
 2STR CU 1/4X5/8C-C C=.48
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Dimensional

Straight
 2.47
 Chamfered
 0.27
 Standard
 0.11
 0.88
 0.48
 0.75
 15/16

Number of Holes

General

2
 CU Compression Terminal Code
 Conductor, Narrow
 Tongue/Beveled Entry, 2
 Hole/W/InspWindow, #2AWG,
 600V-35kV, 1/4" Stud, 0.63
 Spacing, STRD bbl, Tin - Electro
 Plated

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 2 AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin - Electro Plated
 1/4
 Brown
 Y
 10
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175