

Product availability : Stock - Normally stocked in distribution facility



### Main

Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	200 A
System Voltage	120/240 V AC
Mounting mode	Plug-in
Poles description	2P
Circuit breaker type	Standard
Circuit breaker application	HACR rated
Electrical connection	Box lugs

### Complementary

Breaking capacity	10 kA at: 120/240 V AC
Number of spaces required	4
AWG gauge	AWG 1...300 kcmil (copper or aluminium)
Height	3.5 in
Depth	2.91 in
Width	1.5 in

### Environment

Product certifications	CSA UL listed
Ambient air temperature for operation	104 °F (40 °C)

### Ordering and shipping details

Category	00082 - QO BREAKERS 150-200A
Discount Schedule	DE2A

GTIN	00785901755784
Nbr. of units in pkg.	1
Package weight(Lbs)	2.5500000000000003
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------