

Product availability : Stock - Normally stocked in distribution facility



Main

Circuit breaker application	HACR rated
Range of product	QO

Complementary

Line Rated Current	25 A
System Voltage	120/240 V AC
AWG gauge	AWG 14...AWG 8 aluminium/copper
Circuit breaker type	Standard
Electrical connection	Feed-thru lugs
Local signalling	Trip indicator
Mounting mode	Plug-on
Network number of phases	1 phase
Number of poles	2
Number of spaces required	2
Short-circuit protection	10 kA
Product destination	Panelboard NQ/NQOD/Speed-D Load center QO
Protection type	Overload Short-circuit

Environment


Product certifications	CSA UL listed
------------------------	------------------

Ordering and shipping details

Category	00080 - QO SPECIALTY CB,1&2 POLE
Discount Schedule	DE2A
GTIN	00785901755708

Nbr. of units in pkg.	1
Package weight(Lbs)	2.3599999999999999
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------