



[Catalog Home](#)

Product Datasheet

ANDERSON FARGO

GD116 -- Copper Automatic Dead End



Copper Automatic Dead End, Copper, CW Conductor .32 - .33" (8.1 - 8.3 mm), Flex Bail

Product Specifications

Category Image



Automatic Deadends

Copper and Aluminum
AAC, AAAC, ACAR, ACSR,
Copper & Copperweld®
Conductor

Series Image (Automatic)



GD-100 Series

Automatic Dead End

Flex Bail

Copper & Copperweld®
Conductor

PDF Catalog Page

[Click HERE to view the web page.](#)

Bail Option

Flex Bail

Type

Automatic

Material

Copper

Inhibitor Loaded

Yes

Shell Material

Copper Alloy

Bail Material

Stainless Steel

Diameter Range

.32 - .33 in (8.1 - 8.3 mm)

Conductor Range Minimum - Maximum

Cu 1 str (19), Cu 1 str (7), Cu 1/0 sol, CW 3A

Minimum Conductor Diameter

0.32

Maximum Conductor Diameter

0.33

Weight / Ea.

0.63 lbs

Standard Package

25

UPC Code

09635930811

Notes

Add "N" suffix for Neoprene coated bail.

Compressed Product Number

GD116

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.