1/11/2018 Product Details



Product 49121

Number:

Order OTP 1X54T5HO/UNV PSN NL

Abbreviation:

General 1-lamp Universal Voltage electronic ballast for 54W T5HO lamp, packaged 20

Description: pieces per case, without leads

Product Information

Abbrev. With Packaging Info. QTP1X54T5HOUNVPSNNL 20/CS 1/SKU

Ballast Factor 1.00
Ballast Height H (in) 0.8660
Ballast Length L (in) 14.1340
Ballast Width W (in) 1.1810

Family Brand Name QUICKTRONIC Professional

Input Current (Amps) 0.50 Nominal Voltage (V) 120-277V

Number of Lamps 1
Open Circuit Voltage (V) <600
Power Factor >0.98
Primary Lamp Type FP54T5HO

Sound Rating A

Starting Method PROSTART

Starting Temperature - Fahrenheit 0
Starting Temperature - Celsius -18
Total Harmonic Distortion (THD) <10%

Wiring Method WIRETRAP CONNECTORS





Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- · Product is a kit containing the core & coil, capacitor, ingitor (where required), brackets and mounting hardware
- Remote Mounting up to 18 feet
- Remote Mounting up to 12 feet
- Remote Mounting up to 10 feet
- Remote mounting defined by harness length
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Remote Mounting up to 19 feet (keep red wires short for 1&2 lamp).
- Wiring diagram applies to instant start standard, low power (LP), PLUS, and HD10 ballast types.
- · Oil Filled Capacitor
- Product contains installation instructions