



Actual

**Catalog Number:** SL-5  
**Product ID:** 7TAA123920R0004  
**UPC Number:** 78378662919  
**EAN Number:** 05415022249286  
**Status:** Active

5.3 oz. Silicone lubricant for high voltage electrical work.

- Excellent dielectric properties
- Excellent oxidation resistance
- Excellent water repellency
- Resistant to a variety of chemicals
- Compatible with most plastics and rubbers
- Use in the most harsh environments
- Silicone compound is a specially formulated grease product containing selected silicone oils and inert silica fillers.
- This stiff, tacky compound has excellent dielectric properties, oxidation resistance and water repellency.
- It is essentially non-toxic and non-melting and retains its pliability even after extended service.

### North American Specifications (UNSPSC)

UNSPSC	39121337 Electrical sealing compound
IGCC	4496 Electrical sealing compound
Brand Name	Elastimold
Type	Lubricant
Special Features	Specially Formulated for High Voltage Cable.
Application	Heavy Duty Electrical Applications
Size	5.3 oz
Container	Tube
Form	Cream
Material	Silicone Rubber

### Packaging

Outer Quantity	24
Outer Dimensions (inches)	11.5x7.9x8.8
Weight Uom	37.5 lbs. per 100

### Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Safety Data Sheet (SDS) Global	SDS-00031-TB2

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
 www.tnb.com

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: techsupport@tnb.com