



Actual

Catalog Number: **DLC2106**
Product ID: 7TAA267270R0003
UPC Number: 78378684962
Status: Active

Type DLC - Single U-Bolt Aluminum Fittings for Wire Range Main AWG or kcmil 2/0 Stranded - 6 Solid, ASCR Main 2/0 - 6. 1-7/8 inch wide X 1-1/2 inch long X 3-1/4 inch high

North American Specifications (UNSPSC)

UNSPSC	39121408 Mechanical connectors
IGCC	4541 Mechanical connectors
Brand Name	Blackburn
Type	Deadend Loop Connection
Special Features	Top and Bottom Pressure Pads cast of High-Strength, Heat-Treated, Aluminum - Silicon Alloy. Hardware made of Galvanized Steel Provides Added Strength and Durability.
Application	Dead-End Loop Connections
Connection	Mechanical
Number Of Conductors	2
Material	Aluminum
Finish	Bare
Voltage Rating	35kV
Insulation	No
Conductor Range (Main/Primary)	ACSR #2/0 - #6, AWG or KCMIL 2/0 Stranded - #6 Solid
Conductor Range (Tap/Secondary)	ACSR #2/0 - #6, AWG or KCMIL 2/0 Stranded - #6 Solid
Bolt Size	3/8 inch

Packaging

Outer Quantity	50
Outer Dimensions (inches)	8.5x7x6.2
Weight Uom	30.38 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
-----------------------------------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com