



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

**Search Parameters:**

[e-Catalog](#) > [Transformers](#) > [Dry Type, Encapsulated, Enclosed](#)

**Transformers, Dry Type, Encapsulated, Enclosed**

Product #: 9T51B0011

Short Description: 1.5 KVA, 240X480 TO 120/240, 60 HZ

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

Category	Single-Phase:
Phase	1
PriVoltage	240x480
SecVoltage	120/240
KVA	1.5 KVA
Coil Material	CU
TempRise	100 °C
ElecShield	N
SubType	Standard
Frequency	60 Hz
UL	Yes
FrameSize	14200
cUL	Yes
CE	No
Width	9.38 in
Depth	6.72 in
Height	11.12 in
TempClass	180 °C
AmbTemp	40 °C
InsulSys	IS-12
EnergyEfficiency	None
KFactor	K1
Enclosure Type	NEMA 3R
Sound	Std
GSA Compliance	Yes
GO Schedule	90A
List Price	\$382



[View Larger](#)

**Publications/Resources**

[9T51B0011](#)

**Additional Resources for Single-Phase: .050kVA-3kVA and 5kVA-25kVA**

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional](#)  
[Buy Log :8-50](#)

[Control Log : 15-9](#)

These GE transformers feature an encapsulated core and coil in a NEMA 3R non-ventilated weatherproof enclosure.

- UL Listed
- C-UL Listed
- Knockouts provided on back and bottom
- High grade silicon steel core
- Mounting holes on side for easy access
- Wiring compartment includes ground stud

