



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA36LNT38  
7818100210199  
600 CU 1-HOLE NAR.TON. 3  
Active

**Web Use**  
BURNDY Product Line

Tongue Angle  
Length (in)  
Barrell Style  
Bolt Hole Size (in)  
Barrel Type  
Thickness  
B Length (in)  
Pad Width (in)  
Strip Length

**Dimensional**

Straight  
4.09  
Chamfered,Skived  
0.39  
Standard  
0.27  
1.38  
1.12  
1-3/4

Number of Holes  
Product Description

**General**

1  
Flex Conductor Standard Barrel  
Narrow, 600 kcmil, 3/8 in, 4.09 in  
L

Flex (Class G) Size - Range  
Flex (Class H) Size - Range  
Flex (Class I) Size - Range  
Copper Solid Size (Range)  
DLO Size (Range)  
Copper Stranded (Range)

**Conductor(s)**

N/A  
N/A  
N/A  
N/A  
N/A  
600 kcmil

Type of Plating  
Color Code  
Plated (Yes or No)  
Index Number  
Product Material

**Physical**

Tin - Electro Plated  
Green  
Y  
22  
Copper

UL Listed  
CSA Certified  
ROHS Compatible  
UL Recognized  
CULUS

**Approvals / Certifications**

Y  
Y  
Compliant  
N  
N

**Documentation**

**For further technical assistance, please contact us**

**BURNDY LLC - USA**

47 East Industrial Park Drive  
Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
Monday - Friday  
Phone: 800-346-4175