ZCE01

limit switch head ZCE - without lever - spring return - left and right actuation

Product availability : Stock - Normally stocked in distribution facility

Price* : 10.50 USD

Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Rotary head
Product compatibility	XCKD XCMD XCKP XCKT
Associated lever	ZCY23 ZCY55 ZCY59 ZCY25 ZCY19 ZCY46 ZCY45 ZCY22 ZCY53 ZCY54 ZCY39 ZCY48 ZCY26 ZCY12 ZCY49 ZCY18 ZCY91 ZCY69 ZCY17 ZCY16 ZCY81 ZCY15 ZCY44
Associated body	ZCD35 ZCMD21L5

ZCP29
ZCD25
ZCMD37L2
ZCP29M12
ZCT27N12
ZCT28G11
ZCP21M12
ZCMD61C12
ZCT25P16
ZCMD29L5
ZCT21N12
ZCD31
ZCMD29L2
ZCMD39L5
ZCD21M12
ZCP28
ZCMD25L1
ZCD27
ZCMD21C12
ZCMD37L1
ZCMD21L08U78
ZCMD69C12
ZCMD39L1
ZCT25N12
ZCMD81L5
ZCP25
ZCT21G11
ZCMD37L5
ZCMD41L2
ZCMD25L2
ZCMD21M12
ZCD29M12
ZCD28
ZCP21
ZCMD41L1
ZCMD81L2
ZCMD25L5
ZCMD29C12
ZCT27P16
ZCMD29L1
ZCD21
ZCT28N12
ZCT26N12
ZCP31
ZCT26G11
ZCT26P16
ZCMD21L2
ZCP35
ZCP37
ZCMD21L1
ZCT28P16
ZCMD39L2
ZCD29
ZCD26
ZCT25G11
ZCP39
ZCMD41L5
ZCMD61M12
ZCP26
ZCD39
ZCT27G11
ZCD37
ZCMD81L1
ZCMD21L08R12
ZCT21P16
ZCP27

Movement of operating head	Rotary
Type of operator	Without operating lever spring return metal
Type of approach	Lateral approach 2 directions

Complementary

Positive opening	With

Life Is On | Schneider Electric

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22413 - LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	T
GTIN	00785901290483
Nbr. of units in pkg.	1
Package weight(Lbs)	8.9999999999999997E-2
Returnability	Y
Country of origin	ID

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0851 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months