

EASY-WRAP™

Friction, Electrical Filler & Silicone Rubber Tape

EWFT, EWEF, EWSR SERIES



FRICITION TAPE

- Cloth construction offers strong mechanical protection against abrasion and penetration of cable, splices and wire.
- Coated on both sides with a rubber adhesive for adhesion to all types of surfaces.



CAT. NO.	COLOR	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
EWFT 157560	Black	60	0.750	0.015	1

EASY-WRAP™ ELECTRICAL FILLER TAPE

- Butyl based insulation is 1/8" thick for build-up.
- Easy to mold around irregular shapes.
- Self-amalgamates into solid flexible mass.
- Will not corrode copper or aluminum and highly resistant to moisture.
- Rated for applications up to 5 KV.



CAT. NO.	COLOR	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
EWEF 12155	Black	5	1.500	0.125	1

SILICONE RUBBER TAPE - 69 KV

- Self-bonding silicone rubber tape adheres to itself when wrapped under tension and fuses to form a homogeneous mass within 24 hours at room temperature or four hours at 176.6 °C (350 °F).
- No adhesive required; tape leaves no residue.
- Excellent dielectric properties.
- Waterproof and chemical resistant.
- Triangular configuration.

APPLICATIONS:

For use on applications up to 69 KV.
Meets MIL-A-A-59163.

TEMPERATURE RATING:

-53.8 °C to 204.4 (-65 °F to 400 °F).



CAT. NO.	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
EWSR 121030	30	1.000	0.120	1