

## Threaded Couplings

Catalog Number: PRCPLG-1-1/4

UPC: 784011200641

### Description

#### 1-1/4 PVC Coated Coupling

PVC coated rigid metal conduit couplings with urethane interior coating connects coated conduit sections. Electrical continuity is maintained across assembled joints.

### Application

- Connects coated conduit sections while maintaining electrical continuity across assembled joints
- Connects coated conduit sections while maintaining electrical continuity across assembled joints

### Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating over galvanized threads
- 12 trade sizes from 1/2" through 6"
- Sealing sleeves on both ends prevent corrosive liquids and vapors from attacking threaded joints
- Molded external ribs on 1/2" - 4" to prevent tool damage during assembly
- Couplings are straight tapped

### General

Material:	STEEL
Exterior Finish:	A nominal .040 inch (40 mil) gray PVC coating
Interior/Thread Finish:	A nominal .002 inch (2 mil) red urethane coating over galvanized threads

### Dimensions

Metric Size Designators	35
Pipe Size (Inches)	1-1/4
Nominal Weight per 100 (Pounds)	50
Outside Diameter With Rib (Inches)	2.156
Threads Per Inch	11-1/2
Effective Length (Inches) - L2	0.7068
Total Length of Threads to Vanish Point (Inches) - L4	1.0085
Pitch at End of Thread 3/4 in. Taper (Inches) - E0	1.5571



## Threaded Couplings

**Catalog Number:** PRCPLG-1-1/4

**UPC:** 784011200641

### Technical / Specification Documents

---

Specification Guide (1995 Master) *AVAILABLE ON WEBSITE*

---

Specification Guide (2004 Master) *AVAILABLE ON WEBSITE*

---

Installer Certification and Tools *AVAILABLE ON WEBSITE*

---

Chemical Resistance Charts *AVAILABLE ON WEBSITE*

---

Performance Specifications *AVAILABLE ON WEBSITE*

---

### Standards

---

UL 6: E2314

---

CSA Certified: C22.2 No. 45

---

### Notes

---

Couplings are straight tapped.

---

Tolerance, thread length equals plus or minus 1 thread.

---

Plus or minus 1 turn is the maximum variation permitted from the gauging face of the working thread gauges.

---

This is equivalent to plus or minus 1 and 1-1/2 turns from the basic dimensions, since the variation of plus or minus 1/2 turn from basic dimension is permitted in working gauges.

---

