



Catalog No. U055G

Description: 70A SURFACE UNMTRD 50/20

UPC No 784567570601

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors	
Category	Temporary Power
	·
Specifications	
Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	14-50R 5-20R2
Feed	Overhead
AIC	10,000
Amps	70.0 A
Cabinet Size	6 X 14
Circuit Protection	Yes
Hub Provision	No
Installed Breaker	CB250 GFI120
Load Center	LC33N7
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	10.0 lb
Volts	120/240
Classifications	
Standard Package	4
Stock Class Code	Stock
Approvals	
P	
Certification	UL/CUL

midwestelectric.com Created on: 12/13/2021

Publications

TitlePublication No.Publication TypeTemporary Power BrochureFrochure6 pages. MET-019 Rev. B.MET-019ABrochures

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

midwestelectric.com Created on: 12/13/2021