

20 Amp, 125/250, 3Ø 250 and 3Ø 480 Volts AC 3 Pole, 4 Wire, Grounding



20A 125/250V AC NEMA L14-20R 2 (1) HP	20A 3Ø 250V AC NEMA L15-20R 3 HP	20A 3Ø 480V AC NEMA L16-20R 5 HP
---------------------------------------	----------------------------------	----------------------------------




Connector Bodies

Watertight Safety-Shroud®

IP66 SUITABILITY UL Type 4X, 12

Description	Cord Dia.	Catalog Number		
Black Valox® housing, white Valox clamps.	.350"-1.150" (9-29)	HBL2413SW	HBL2423SW	HBL2433SW



HBL2423SW

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2413	HBL2423	HBL2433
Black and white nylon, spring termination.	.350"-1.150" (9-29)	HBL2413ST	HBL2423ST	HBL2433ST
Spring termination, all black.	.350"-1.150" (9-29)	HBL2413STBK	—	—
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	HBL24CM13	HBL24CM23	HBL24CM33
All black nylon.	.350"-1.150" (9-29)	HBL2413BK	—	—



HBL2413

Note: See pages C-52 and C-53 for accessories.

Receptacles

Watertight Safety-Shroud

IP66 SUITABILITY UL Type 4X, 12

Description	Catalog Number		
Gray Valox housing and flange, back wired.	HBL2410SW	HBL2420SW	HBL2430SW

Note: See page C-54 for accessories.

Safety-Shroud® Twist-Lock®

IP20 SUITABILITY

Description	Catalog Number		
Gray Valox angle housing, one gang, back wired.	HBL2410AR	HBL2420AR	HBL2430AR
Gray Valox surface mounting, one gang, back wired.	HBL2410SR	HBL2420SR	HBL2430SR
Gray Valox semi-flush, two gang, back wired.	HBL2410SR2	HBL2420SR2	HBL2430SR2



HBL2420SW

Single Flush Receptacles

IP20 SUITABILITY


Description	Catalog Number		
Black nylon face, back and side wired.	HBL2410	HBL2420	HBL2430
Black and white nylon, spring termination.	HBL2410ST	HBL2420ST	HBL2430ST
Isolated ground, orange nylon face, back and side wired.	IG2410	IG2420	—
Isolated ground, spring termination.	—	IG2420ST	—
Ring terminal connection.	HBL2410RT	HBL2420RT	—

Note: See page C-52 for accessories.


Insulgrip® Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	HBL2416	HBL2426	HBL2436
Nylon casing, back wire, spring terminatio.	HBL2416ST	HBL2426ST	HBL2436ST


Note: See page C-52 for accessories.




HBL2430ST




HBL2416



HBL2410



HBL2420SR2



HBL2420SR

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)