Product data sheet Characteristics

QU12L400CL METER MAIN 400A RINGLESS

Product availability: Stock - Normally stocked in distribution facility





Main

Product or component type	Meter Mains	
Range of product	QO	

Complementary

Complementary		3
Line Rated Current	400 A	
Short-circuit current	25 kA	<u></u>
Meter socket type	Ringless	
Device mounting	Surface Semi flush field installed flange kit	
Number of spaces	0	
Number of circuits	0	
Product mounting	Surface Semi-flush with field installed flange kit	
Number of tandem circuit breakers	0	و =
Hub type	A-L	t
Electrical connection	Lugs service ground Studs line side	
AWG gauge	AWG 4250 kcmil (aluminium) service ground AWG 4250 kcmil (copper) service ground	etiinte fo
Device composition	Service disconnect (factory installed)	
Service disconnect rated current	200 A	v
Service feed location	UG	
Bypass type	Class 320 lever bypass	<u>ء</u>

Ordering and shipping details

Category	00022 - QO METER MAINS	-
Discount Schedule	DE3A	
GTIN	00785901421009	
Nbr. of units in pkg.	1	

0 -1-1	N (0	
Offer Sustainability		
Country of origin	MX	
Returnability	Υ	
Package weight(Lbs)	112	

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014
	Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold

Contractual	warrantv

Warranty period	18 months