







DIP MOLDED SIZES 1/2 THRU 6

NOTES:

- 1. COUPLING IS PVC COATED ALUMINUM PIPE.
- 2. BLUE URETHANE COATING ON INTERIOR OF COUPLING.
- 3. PVC COATING ON EXTERIOR OF COUPLING, .040" (40 MIL) MINIMUM. PVC SLEEVES ON EACH END OF COUPLING.
- 4. COLOR CODED THREAD PROTECTORS INSERTED IN EACH SLEEVE.

| GENERAL NOTES | | | | Thomas@Betts | |
|--|--|-----------|----------|--------------|--|
| ALL DIMENSIONS ARE FOR REFERENCE ONLY. DIMENSIONS IN BRACKETS [] | www.tnb.com A Member of the ABB Group | | | | |
| ARE IN METRIC UNITS. | PVC COATED COUPLING | | | | |
| REVISIONS | | | | | |
| ² SEE ERN 2018670 | | | | | |
| FOR APPROVAL SIGNATURES & RELEASE DATE. PROJECT NO: 087M001467 | ORIGINAL PROJECT NO / (ERN NO) | SHEET NO: | REV. NO: | DRAWING NO: | |
| | RM401877 / (2011363) | 1 OF 2 | 2 | WSD-000546 | |

| CATALOG NUMBER | TRADE SIZE | MIN. LENGTH OF COUPLING | MIN. SLEEVE EXTENSION LENGTH |
|----------------|------------|----------------------------|---------------------------------|
| CPL1/2SA-X | 1/2 [16] | 1-5/8 [41.27] | 1/2 [12.70] |
| CPL3/4SA-X | 3/4 [21] | 1-41/64 [41.67] | 3/4 [19.05] |
| CPL1SA-X | 1 [27] | 1-31/32 [50.00] | 1 [25.40] |
| CPL11/4SA-X | 1-1/4 [35] | 2-1/32 [51.59] | 1-1/4 [31.75] |
| CPL11/2SA-X | 1-1/2 [41] | 2-1/16 [52.38] | 1-1/2 [38.10] |
| CPL2SA-X | 2 [53] | 2-1/8 [53.97] | 2 [50.80] |
| CPL21/2SA-X | 2-1/2 [63] | 3-3/16 [80.96] | 2 [50.80] |
| CPL3SA-X | 3 [78] | 3-5/16 [84.13] | 2 [50.80] |
| CPL31/2SA-X | 3-1/2 [91] | 3-13/32 [86.51] | 2 [50.80] |
| CPL4SA-X | 4 [103] | 3-33/64 [89.29] | 2 [50.80] |
| CPL5SA-X | 5 [129] | 3-61/64 [100.40] | 2 [50.80] |
| CPL6SA-X | 6 [155] | 4-1/4 [107.95] | 2 [50.80] |



