

**Catalog Number:** XJG44-TB  
**Product ID:** 7TAD013860R0005  
**UPC Number:** 78621088094  
**Status:** Active



1-1/4 Inch XJG Conduit Expansion Coupling with Internal Bonding Jumper, Body Malleable Iron Zinc Plated, Internal Bonding Jumper Tinned Copper Braid, Packing PTFE/Synthetic Fiber Material, 4 Inch Movement

- True Internal Bonding Jumper-no external grounding strap required, tamper-proof internal jumper protected from the environment.
- Exceeds code requirements for long conduit runs to permit linear movement.

Actual



Representative

## North American Specifications (UNSPSC)

UNSPSC	39131707 Electrical conduit coupling
IGCC	5548 Electrical conduit coupling
Brand Name	T&B
Type	XJG Expansion Couplings
Special Features	No Disassembly Necessary to Install. Fast, Simple, and Requires Fewer Steps
Application	Allows for The Contraction and Expansion of a Conduit Run Without Reducing The Mechanical or Bonding Integrity of The Raceway
Standard	UL E23018, CSA
Trade Size	1-1/4 Inch
Outside Diameter	3.36 Inch
Length	10.56 in
Material	Malleable Iron

## European Specifications (ETIM)

ETIM	EC000939 Coupler for installation tubes
Material	Metal
Material quality	Other
Surface protection	Other
Model	Thread
Two piece	N
With inspection opening and cover	N

## Packaging

Outer Quantity	1
Outer Dimensions (inches)	10.5x6.5x4.62
Weight Uom	8.25 lbs. Each

## Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA02289-TB2

## Header

3D Model	Available on Website
----------	----------------------

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)