



Compression Splice Full Tension

by FARGO
Catalog ID: 811630

Compression Splice, Static Wire, Full Tension, for EHS Steel, Alumoweld(R), Dia. Range 0.417-0.438



* Representative image

Product Details

General

Compression Method	Single Die
Material	Aluminum Alloy
Press Minimum	60 to
Tension Range	0 lb
UPC	096359251644

Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	12.8 in
Weight	0.490 lb

Conductor Related

Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Diameter - Maximum	0.438 in
Conductor Diameter - Minimum	0.417 in
Conductor Diameter Range	0.417 - 0.438
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

Certifications and Compliance

UL Listed	No
-----------	----

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscsc@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com