



**POWER
SYSTEMS, INC.**

In the world of power transmission and distribution, look to Hubbell

**Interactive
eCatalog**

[Catalog Home](#)

Product Datasheet

ANDERSON FARGO

C151212 -- Compression Splice



Compression
Splice, Uni-
Grip, Full
Tension, for
AAC, Dia.
Range
1.046-1.140

Product Specifications

Splice Type



Transmission
Compression
Splices

Transmission Compression Series



C15 Series

Compression Splice
Uni-Grip® (One Die)
Full Tension
AAC Conductor

PDF Catalog Page

[Click HERE to view the web page.](#)

Conductor Type

AAC

Conductor Diameter (Minimum)

1.046 in

Conductor Diameter (Maximum)

1.14 in

Material

Aluminum Alloy

Minimum Conductor Diameter

1.046 in

Maximum Conductor Diameter

1.14 in

Length before Compression

14.4 in (365 mm)

Compression Method

Uni-Grip (single die system)

Die Size

12CD

Minimum Press (Tons)

60

Voltage Application

EHV & Std

UL Listed

No

Inhibitor Loaded

Yes

Material Type

Non-Standard

UPC Code	09635929422
Standard Package	3
Standard Package Unit	Each
Min Order Qty	1
Weight / Ea.	2.205 lbs

Notes

For extra length repair splice, add suffix "XL-XX" where XX is repair cutoff length in inches (max 60).

Compressed Product Number

C151212

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.