



[Catalog Home](#)

**Product Datasheet**

**ANDERSON FARGO**

**GD113 -- Copper Automatic Dead End**



Copper Automatic Dead End, Copper, CW Conductor .22 - .23" (5.7- 5.9 mm), Flex Bail

**Product Specifications**

Category Image



**Automatic Deadends**  
Copper and Aluminum  
AAC, AAAC, ACAR, ACSR,  
Copper & Copperweld®  
Conductor

Series Image (Automatic)



**GD-100 Series**  
**Automatic Dead End**  
Flex Bail  
Copper & Copperweld®  
Conductor

PDF Catalog Page

[Click HERE to view the web page.](#)

Bail Option

Flex Bail

Type

Automatic

Material

Copper

Inhibitor Loaded

Yes

Shell Material

Copper Alloy

Bail Material

Stainless Steel

Diameter Range

.22 - .23 in (5.7 - 5.9 mm)

Conductor Range Minimum - Maximum

Cu 3 sol, Cu 4 str (7), CW 6A

Minimum Conductor Diameter

0.22

Maximum Conductor Diameter

0.23

Weight / Ea.

0.2 lbs

Standard Package

100

UPC Code

09635930796

**Notes**

Add "N" suffix for Neoprene coated bail.

**Compressed Product Number**

GD113

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

*All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.*

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.