

# Product data sheet

## Characteristics

# 1S1F

## TRANSFORMER DRY 1KVA

### 240X480V-120/240V

Product availability : Stock - Normally stocked in distribution facility



Price\* : 602.00 USD



### Main

Product or component type	Dry Sealed Transformer
Primary voltage	240 x 480 V
Secondary voltage	120/240 V
Number of tap-offs	0

### Complementary

Box number	7A
Phase	1 phase
Primary voltage	240 x 480 V : 120/240 V
Rated power in VA	1 kVA
Temperature rise	115 °C
Height	8.13 in
Width	6.94 in
Depth	5.31 in
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

### Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CULus CSA UL listed

### Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
----------	-------------------------

Discount Schedule	PE2
GTIN	00785901019862
Nbr. of units in pkg.	1
Package weight(Lbs)	24.77
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------