Product data sheet Characteristics

9001KP1A31 PILOT LIGHT 120VAC 30MM TYPE K +OPTIONS

Product availability: Stock - Normally stocked in distribution facility



Price*: 153.00 USD



Main

Range of product	Harmony 9001K	
Product or component type	Pilot light	
Device short name	К	

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Lens type	Fresnel (plastic)	
Cap/Operator or lens colour	Amber	
Light source	Incandescent	
Bulb base	BA 9s	
Light block supply	Via transformer 120 V AC (f = 50/60 Hz) Via integral transformer 110 V AC (f = 50/60 Hz)	:
Connections - terminals	Screw clamp terminals (1 x 0.222 x 1.5 mm²) conforming to IEC 60947-1	
Shape of screw head	Round head	
Operating position	Any position	
[Us] rated supply voltage	110120 V AC	
Operating mode	Normal	
Device presentation	Complete product	

Environment

Product certifications	CE	e Paris
	UL listed file E42259 CCN NKCR	<u> </u>
	CSA LR25490 class 3211 03	Ö
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13	
NEMA degree of protection	NEIVIA 1/2/3/3R/4/0/12/13	

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	00785901032038
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5
Returnability	Υ
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months