

Product availability : Stock - Normally stocked in distribution facility



Price\* : 509.00 USD



### Main

Product or component type	Industrial Control Transformer
Rated power in VA	500 VA
Primary voltage	208/240/277/380/480 V
Secondary voltage	24 V
Range of product	T

### Complementary

Phase	1 phase
Rated power in VA	500 VA per UL 500 VA per CSA 500 VA per NOM 300 VA per CE
Primary voltage	208/240/277/380/480 V : 24 V
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	4.51 in
Width	5.25 in
Depth	5.61 in
Material	Copper winding
Product compatibility	FSC23

### Environment

Product certifications	CE UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

## Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901039303
Nbr. of units in pkg.	1
Package weight(Lbs)	17.699999999999999
Returnability	Y
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	10 years
-----------------	----------