Product data sheet Characteristics

9001SKP35G31 PILOT LIGHT 28V 30MM SK +OPTIONS

Product availability: Stock - Normally stocked in distribution facility



Price*: 125.00 USD



Main

Product or component type	Pilot light	
Lens type	Fresnel plastic	
Light block supply	Full voltage 28 V Direct 24 V	

Complementary

		y
		. <u>.</u> 1
		i.
		و با
Main		90
Product or component type	Pilot light	ı, ı
Lens type	Fresnel plastic	
Light block supply	Full voltage 28 V Direct 24 V	This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for shorting the sample of the sa
		i i
Complementary		
Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	: : :-
Shape of signaling unit head	Round	ט ב <u>.</u>
Cap/Operator or lens colour	Green	
Light source	Incandescent	
Bulb base	BA 9s	,
[Us] rated supply voltage	2428 V AC/DC	
Operating position	Any position	
Operating mode	Normal	<u>».</u> 3
CAD overall width	2.13 in (54 mm)	
CAD overall height	2.76 in (70 mm)	
CAD overall depth	1.65 in (42 mm)	
Device presentation	Complete product	0
Environment		### ### ### ### ### ### ### ### ### ##
Protective treatment	TC	
IP degree of protection	IP66	in the state of th
<u> </u>		
		5 7
Ordering and shipping details	0.100 000 01/01/01	
Category	21429 - 9001 SK,SKY	a La
Discount Schedule	CS1	<u></u>

Environment

	· · · · · · · · · · · · · · · · · · ·
Protective treatment	TC
IP degree of protection	IP66

Ordering and shipping details

Cracing and ompping ac	tano	⊢
Category	21429 - 9001 SK,SKY	
Discount Schedule	CS1	SOB

GTIN	00785901041313	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.179999999999999	
Returnability	Υ	
Country of origin	MX	
Offer Sustainability		
Offer Sustainability RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity	
	Compliant - since 0921 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	
	_ '	

18 months

Warranty period