

Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|-----------------------------------|---|
| Product or component type | Load Center |
| Range of product | QO |
| Load center type | Main lugs |
| Line Rated Current | 60 A |
| Number of spaces | 3 |
| Short-circuit current | 65 kA |
| Number of circuits | 3 |
| Number of tandem circuit breakers | 0 |
| Phase | 3 phases |
| System Voltage | 208Y/120 V AC 240/120 V delta AC 240 V delta AC |

Complementary

| | |
|---------------------------|-----------------------------|
| AWG gauge | AWG 10...AWG 6 (copper) |
| NEMA degree of protection | NEMA 1 indoor |
| Cover type | Surface cover |
| Electrical connection | Lugs |
| Device composition | Neutral (factory installed) |
| Electrical connection | Lugs |
| Wiring configuration | 4-wire 3-wire |
| Material | Tin plated aluminium busbar |
| Enclosure material | Welded sheet steel |
| Surface finish | Baked enamel grey |
| Box number | 13 |
| Product certifications | UL listed |
| Height | 13.11 in (333 mm) |
| Width | 5.87 in (149 mm) |

Ordering and shipping details

| | |
|-----------------------|-----------------------------------|
| Category | 00011 - QO 3PH LOAD CENTER,INDOOR |
| Discount Schedule | DE3 |
| GTIN | 00785901051701 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 5.7400000000000002 |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1248 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|