


Product availability : Stock - Normally stocked in distribution facility



Price* : 32.70 USD



Main

Range of product	Power Relay 8501C
Product or component type	Power relay
Device short name	Type C
Line Rated Current	30 A
Device application	Suited for controlling small single phase motors and other light loads
[Uc] control circuit voltage	240 V AC at 50/60 Hz
Rated power in hp	2 hp
Maximum switching voltage	600 V AC

Complementary

Catalog class	8501
Switch function	SPST
Contacts type and composition	1 NO
Mounting support	Panel mounting
Phase	1 phase
Connections - terminals	Screw clamp terminal

Environment

Product certifications	CSA UL listed CE
Ambient air temperature for operation	-22...122 °F

Ordering and shipping details

Category	21131 - 8501 C
Discount Schedule	CP2
GTIN	00785901052043

Nbr. of units in pkg.	1
Package weight(Lbs)	0.56000000000000005
Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------