# Product data sheet Characteristics

# **QO2100VH**

# QO Miniature Circuit Breaker 100A 2P 120/240V 22kA Plug-in Mount

Product availability: Stock - Normally stocked in distribution facility







### Main

Main		
Product or component type	Miniature circuit-breaker	
Range of product	QO	
Line Rated Current	100 A	
System Voltage	120/240 V AC	
Mounting mode	Plug-in	
Poles description	2P	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	
Electrical connection	Box lugs	
Complementary Breaking capacity	22 kA at: 120/240 V AC	
Number of spaces required	2	
AWG gauge	AWG 4AWG 2/0 (copper or aluminium)	
Height	3.5 in	
Depth	2.91 in	
Width	1.5 in	
Environment		
Product certifications	UL listed CSA	
Ambient air temperature for operation	104 °F (40 °C)	
Ordering and shipping details		
Category	00926 - QO IND SPECIALTY CB	
Discount Schedule	DE2A	
Con 20, 2047		

#### Complementary

Breaking capacity	22 kA at: 120/240 V AC
Number of spaces required	2
AWG gauge	AWG 4AWG 2/0 (copper or aluminium)
Height	3.5 in
Depth	2.91 in
Width	1.5 in

#### Environment

Product certifications	UL listed CSA
Ambient air temperature for operation	104 °F (40 °C)

### Ordering and shipping details

<u> 0 11 0</u>	
Category	00926 - QO IND SPECIALTY CB
Discount Schedule	DE2A

GTIN	00785901054924
Nbr. of units in pkg.	1
Package weight(Lbs)	0.7299999999998
Returnability	Υ
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period 18 months
---------------------------