

3S67F

TRANSFORMER DRY 3KVA MULTIPLE VOLTAGES

Product availability : Stock - Normally stocked in distribution facility



Price* : 2290.00 USD



Main

Primary voltage	190/200/208/220 x 380/400/416/440 V
Secondary voltage	110/220 V
Number of tap-offs	0

Complementary

Box number	10A
Phase	1 phase
Primary voltage	190/200/208/220 x 380/400/416/440 V : 110/220 V
Rated power in VA	3 kVA
Temperature rise	115 °C
Height	10.5 in
Width	8.62 in
Depth	6.5 in
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	TÜV cULus UL listed CSA

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
----------	-------------------------

Discount Schedule	PE2
GTIN	00785901069478
Nbr. of units in pkg.	1
Package weight(Lbs)	59.70000000000003
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------