

Interactive @Catalog

Catalog Home

Product Datasheet

CHANCE

126542AE -- Square Shaft (SS 5) Lead Section with Guy Adapter Twineye

Lead Section Guy Adapter



Square Shaft (SS 5) Lead Section, 3' (914 mm) long with 8" (203 mm) - 10" (254 mm) Helices with Guy Adapter Twineye in separate box

Square Shaft (SS 5) Anchor	
Lead Section W/Guy Adapter	
2	
8" (203 mm) - 10" (254 mm)	
Twineye	
3' (914 mm)	
70,000 lbs (311.4 kN)	
5,500 Ft Lbs (7,457 N-M)	
Galvanized	
Non-Standard	
09635906848	
1	
EA	
1	
90.65 lbs	
Click <u>HERE</u> to view the web page.	
Click HERE to view drawing.	
	Lead Section W/Guy Adapter 2 8" (203 mm) - 10" (254 mm) Twineye 3' (914 mm) 70,000 lbs (311.4 kN) 5,500 Ft Lbs (7,457 N-M) Galvanized Non-Standard 09635906848 1 EA 1 90.65 lbs Click HERE to view the web page.

Notes

Caution: All components of the Chance anchoring system are performance mated. Use of other anchoring products or equipment will not necessarily produce the same results.

Compressed Product Number

126542AE

Strength Note

Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength. Note: Pulling Eye Rated: 12,000 lbs. Guy wire should not be attached to pulling eye.

Catalog Home



Warranty Info | **Trademarks** | **Terms of Use**

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.